

CB-B 低压齿轮泵

CB-B LOW PRESSURE GEAR PUMPS

德力液压 Deli®

简介 General Description

CB-B 低压齿轮泵是由一对相互啮合的齿轮，一个泵体、一个前盖和一个后盖组成。该系列低压齿轮泵结构简单，工作可靠。不但具有高机械效率和容积效率，同时还具有低噪声和低重量功率比。CB-B 齿轮泵被广泛的应用于机床、塑料机械和矿山机械中。


The CB-B gear pump consists of a gear pair, a housing, a front cover and a rear cover. The CB-B Gear Pump features high mechanical and volumetric efficiency, low noise level as well as low weight/power ratio. It is widely used in machine tools, plastic machine and mining machine.



型谱 Order Code

CB-B * *		旋向 Direction	空位 Orbit	
2.5MPa	额定压力 Rated pressure		F	顺时针 CW 逆时针 CCW
2.5 ~ 125L/min	公称流量 Flow			

外形尺寸图 Outline Dimension



技术参数 Technical Data

Model 型号	C	E	H	C ₁	C ₂	D	D ₁	d (h6)	E ₁	T	b	M	K ₁	K ₂	Flow 流量 (L/min)	Pressure 压力 (MPa)	Speed 转速 (RPM)	Efficiency 容积效率	Weight 重量 (Kg)	Power 功率 (Kw)
CB-B2.5	75	65	95	21	26	$\phi 35^{-0.025}_{-0.050}$	$\phi 50$	$\phi 12$	35	30	4	M6	$Z3/8"$	$Z3/8"$	2.5	75%	1450	2.5	0.13	
CB-B4	79			22	27															
CB-B6	86			25	30														2.8	0.21
CB-B10	93			24	29														3.2	0.31
CB-B16	107	86	128	30	35	$\phi 50^{-0.009}_{-0.025}$	$\phi 65$	$\phi 16$	50	42	5	M8	$Z3/4"$	$Z3/4"$	16	80%	1450	2.5	5.2	1.82
CB-B20	111																		2.8	0.21
CB-B25	115																		3.2	0.31
CB-B32	121																		3.5	0.51
CB-B40	132	100	152	35	40	$\phi 55^{-0.010}_{-0.029}$	$\phi 80$	$\phi 22$	55	52	6	M8	$Z1"$	$Z1"$	40	90%	1450	2.5	5.2	1.82
CB-B50	138																		5.4	1.02
CB-B63	144																		5.5	1.30
CB-B80	158																		6.0	1.65
CB-B100	165	120	185	45	50	$\phi 70^{-0.010}_{-0.029}$	$\phi 95$	$\phi 30$	65	79	8	M8	$Z1\frac{1}{4}"$	$Z1"$	80	90%	1450	2.5	10.5	2.10
CB-B125	174																		11.0	2.60
																		11.8	3.30	
																		17.6	4.10	
																		18.7	5.10	
																		19.5	6.50	